

## CO<sub>2</sub> FIRE EXTINGUISHER MS1539



TECHNICAL SPECIFICATION		
Code No.	FEX139-CS-020-RD	FEX139-CS-050-RD
Material	Carbon Steel	
Capacity	2 kg	5 kg
Operating Pressure	60 bar at 27°C	
Overall Height	530 mm	770 mm
Overall Diameter	113 mm	140 mm
Cylinder Test Pressure	250 bar	
Discharge Time (min.)	6 secs	9 secs
Standard	Manufactured & approved to MS1539 Part 1	
Full Weight	7.7 kg	17.5 kg
Paint Finish	Red	
Fire Rating	21B	55B
Operating Temperature	-20°C to 60°C	
Discharge Range (approx)	3 m	
Carton Size	180 x 195 x 665 mm	230 x 230 x 715 mm

## WET CHEMICAL FIRE EXTINGUISHER MS1539



TECHNICAL SPECIFICATION		
Code No.	FEX127-SS-2LT-RD	FEX128-MS-6LT-RD
Type of Extinguishant	Wet Chemical	
Capacity	2.0L +0% , -5%	6.0L +0% , -5%
Propellant	Nitrogen	
Cylinder Diameter (Ø D)	Ø118.0 ±1.0mm	Ø160.0 ±1.0mm
Overall Height (H)	430.0 ±2.0mm	520.0 ±5.0mm
Overall Weight	9.2kg +2% , -0%	10.6kg +2% , -0%
Volume	2L	6L
Min. Test Pressure	25bar (362.5psi) min 30s	
Working Pressure	12bar (174.0psi)	
Discharge Time (min.)	Minimum 25sec	Minimum 40sec
Class of Fire	5A , 5F	8A, 75F
Temperature Range	+5°C to +60°C	+5°C to +60°C
Design	Manufactured and Approved to MS 1539	
Paint Finish	Red	